

Washdown Duty



Washdown Duty

ABB's Baldor-Reliance washdown motors are highly durable and resistant to harsh cleaning environments. With robust enclosures and corrosion-resistant materials, they perform reliably in industries with stringent hygiene standards, like food and beverage processing. Adhering to NEMA efficiency standards, they ensure longevity and efficiency in demanding applications.



Food Safe stainless steel, single phase



Food Safe stainless steel, encapsulated, three phase



Stainless Steel, three phase



Paint Free, three phase



White Washdown, single phase



White Washdown, three phase



White Washdown Features, three phase



Washdown lead connection kits

Product Line		Food Safe Washdown	Stainless steel	Paint free	White Washdown	White WD features
Frame Sizes	NEMA Frames sizes	56-286TC	56C-256TC	56C-256TC	56-256TC	254-444TC
Electrical features						
Efficiency	Baldor-Reliance motors meet or exceed all efficiency requirements for US, Canada and Mexico regulations	S	S	S	S	S
Motor performance	1.15 Service Factor	S	S	S	S	S
	NEMA Design B (most designs)	S	S	S	S	S
Windings	Class F insulation with Class B rise (most designs)	-	S	S	S	S
	Class H insulation	S	A	A	A	A
	Dip & bake 100% varnish	S	S	S	S	S
	Epoxy encapsulated	S	A	A	A	-
	Single Phase	S	-	-	S	-
Connections	Washdown lead connection kit (heat shrink connectors)	S	A	A	A	A
Inverter	Inverter ready per NEMA MG-1 part 31.4.4.2	S	S	S	S	S
Mechanical features						
External parts	Steel frame and base, aluminum box and endplates	-	-	-	S	-
	300 series stainless steel shaft & hardware	S	S	S	S	S
	Polished head, 300 series stainless steel external hardware & drains	S	-	-	-	-
	Ball burnished aluminum endplates and conduit box	-	-	S	-	-
	300 series endplates and conduit box	S	S	-	-	-
	300 series stainless stator frame, conduit box lid and fan cover	S	S	S	-	-
Drains	3 removable plastic condensation drain plugs, each end	-	-	-	S	S
	3 removable stainless steel condensation drain plugs, each end	S	S	S	-	-
	1 extra plastic T-drain provided, each end (for 6:00 position)	S	S	S	S	S
	Stainless steel T-drains installed at 6:00, 180 frame and larger	S	-	-	-	-
Nameplate	Stainless steel nameplate affixed to band	-	-	S	S	S
	Nameplate information laser etched directly onto band	S	S	-	-	-
Conduit box	Neoprene, lipped box-to-stator gasket	-	S	S	S	S
	180° rotatable conduit box	-	S	S	S	S
	Lipped lid w/neoprene gasket	-	S	S	S	S
	Round conduit box, fully rotatable	S	-	-	-	-
	Epoxy encapsulated leads in box	S	-	-	-	-
	Fully welded conduit box	S	-	-	-	-
Rotor	Epoxy primed rotor	S	S	S	S	S
Lubrication	Mobil Polyrex™ EM moisture resistant grease	S	S	S	S	S
Cooling	Non-metallic external cooling fan	S	S	S	S	S
Base	Standard welded base	-	S	S	S	-
	Individual, fully welded feet for ease of cleanability	S	-	-	-	-
	Cast base	-	-	-	-	S
Sealing	Lip & V-Ring seal on drive end, V-Ring seal on opposite drive end (TEFC)	-	-	-	S	S
	Labyrinth seal on drive end, V-Ring seal on opposite drive end (TEFC)	-	-	S	A	A
	Labyrinth seal on each end (TEFC)	-	S	A	A	A
	2-part sealing system (internal & external seals) on each end (TEFC)	S	-	-	-	-
	Sealer on endplate-to-stator fits	-	S	S	S	S
	O-Rings on endplate-to-stator fits	S	-	-	-	-
Paint	White epoxy, corrosion resistant finish	-	-	-	S	S
IP code	Ingress protection code	IP69 for water	IP56	IP55	IP55	IP55

S = Standard A = Available through Mod Express® or as custom

Food Safe stainless steel, single phase

1/2 thru 1 Hp

Features

- 300 series stainless steel
- Individually welded feet for ease of cleaning, Smooth heads on external drains & hardware
- Welded & polished conduit box
- Laser marked nameplate
- O-ring sealed endplates
- Internal & external shaft sealing
- 3 year warranty, NEMA Premium® efficiency

Applications

- Caustic environment
- Food processing
- High pressure washdown
- Outdoors
- Pumps and wastewater
- Sanitary washdown

IP69

Food Safe stainless steel, single phase, C-face foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
115/230 volt												
1/2	3600	56C	TEFC	CFSWDL3503	2,289	WDF	13.96	33	59.5	115/230	3.6	12
	1800	56C	TEFC	CFSWDL3504	2,453	WDF	13.96	41	70.0	115/230	3.5	
3/4	3600	56C	TEFC	CFSWDL3506	2,534	WDF	13.96	33	64.0	115/230	4.6	12
	1800	56C	TEFC	CFSWDL3507	2,683	WDF	14.83	47	70.0	115/230	4.6	
1	3600	56C	TEFC	CFSWDL3509	2,705	WDF	13.96	41	68.0	115/230	5.8	12
	1800	56C	TEFC	CFSWDL3510	2,885	WDF	16.26	62	74.0	115/230	5.5	

Food Safe stainless steel, single phase, C-face footless



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
115/230 volt												
1/2	3600	56C	TEFC	VFSWDL3503	2,163	WDF	13.96	33	59.5	115/230	3.6	12
	1800	56C	TEFC	VFSWDL3504	2,327	WDF	13.96	41	70.0	115/230	3.5	
3/4	3600	56C	TEFC	VFSWDL3506	2,408	WDF	13.96	33	64.0	115/230	4.6	12
	1800	56C	TEFC	VFSWDL3507	2,557	WDF	14.83	47	70.0	115/230	4.6	
1	3600	56C	TEFC	VFSWDL3509	2,579	WDF	13.96	41	68.0	115/230	5.8	12
	1800	56C	TEFC	VFSWDL3510	2,759	WDF	16.26	63	74.0	115/230	5.5	

TOC
INFO
SP4
GP
SD
WD
XP
PUMP
HVAC
FARM
DP
UH
BRM
VSAC
IMD
DCPM
DCSW
GRDS
BUFF
LATH
GBPA
ACPA
DCPA
ACC
MDEX
INDX
NOTE

Food Safe stainless steel, encapsulated, three phase 1/2 thru 30 Hp

IP69

Features

- 300 series stainless steel
- Individually welded feet for ease of cleaning, Smooth heads on external drains & hardware
- Welded & polished conduit box 360° rotatable
- Epoxy encapsulated windings with Class H insulation system, Encapsulated, color-coded leads
- O-ring sealed endplates
- Internal & external shaft sealing
- 3 year warranty, NEMA Premium® efficiency

Applications

- Caustic environment
- Food processing
- Pumps and wastewater
- Outdoors
- High pressure washdown
- Sanitary washdown

Food Safe stainless steel, three phase, foot mounted, encapsulated



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	1800	56	TENV	FSWDM3538-E	2,673	WDF	11.78	35	80.0	208-230/460	0.9	
3/4	1800	56	TENV	FSWDM3542-E	2,766	WDF	12.78	37	84.0	208-230/460	1.3	
1	1800	56	TENV	FSWDM3546-E	2,892	WDF	12.78	41	85.5	230/460	1.7	30
		143T	TENV	FSWDM3546T-E	2,915	WDF	12.84	41	85.5	230/460	1.7	30
1 1/2	1800	145T	TEFC	FSWDM3554T-E	3,178	WDF	14.03	45	86.5	230/460	2.2	30
2	1800	145T	TEFC	FSWDM3558T-E	3,652	WDF	14.03	50	86.5	230/460	2.7	30
3	1800	182T	TEFC	FSWDM3611T-E	4,350	WDF	18.89	86	89.5	230/460	4.2	30
5	1800	184T	TEFC	FSWDM3615T-E	4,647	WDF	18.89	101	89.5	230/460	6.5	30
7 1/2	1800	213T	TEFC	FSWDM3710T-E	5,888	WDF	19.93	136	91.7	230/460	9.5	
10	1800	215T	TEFC	FSWDM3714T-E	6,958	WDF	21.37	187	92.4	230/460	12.5	30
15	1800	254T	TEFC	FSWDM23933T-E	11,294	WDF	24.18	304	92.4	230/460	17.5	30
20	1800	256T	TEFC	FSWDM23934T-E	12,946	WDF	25.18	287	93.0	230/460	24.0	
25	1800	284T	TEFC	FSWDM41903T	16,573	WDF	28.14	378	93.6	230/460	30.0	22
30	1800	284T	TEFC	FSWDM41904T	19,094	WDF	28.14	395	93.6	230/460	37.0	22

Food Safe stainless steel, three phase, C-face foot mounted, encapsulated



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	3600	56C	TENV	CFSWDM3537-E	2,691	WDF	11.78	35	84.0	208-230/460	0.7	30
	1800	56C	TENV	CFSWDM3538-E	2,731	WDF	11.78	38	80.0	208-230/460	0.9	
	1200	56C	TENV	CFSWDM3539-E	3,281	WDF	12.78	37	77.0	208-230/460	0.9	
3/4	3600	56C	TENV	CFSWDM3541-E	2,781	WDF	11.78	41	86.5	208-230/460	1.0	30
	1800	56C	TENV	CFSWDM3542-E	2,824	WDF	12.78	37	84.0	208-230/460	1.3	
	1200	56C	TENV	CFSWDM3543-E	3,372	WDF	13.67	45	82.5	208-230/460	1.3	
1	3600	56C	TENV	CFSWDM3545-E	2,920	WDF	11.78	38	82.5	230/460	1.4	30
	1800	56C	TENV	CFSWDM3546-E	2,950	WDF	12.78	37	85.5	230/460	1.7	30
		143TC	TENV	CFSWDM3546T-E	2,973	WDF	12.84	37	85.5	230/460	1.7	30
	1200	56C	TEFC	CFSWDM3556-E	3,487	WDF	14.83	45	82.5	230/460	1.7	30
1 1/2	3600	56C	TENV	CFSWDM3550-E	3,087	WDF	13.67	50	85.5	230/460	1.8	30
		143TC	TENV	CFSWDM3550T-E	3,112	WDF	13.72	50	85.5	230/460	1.8	30
	1800	56C	TEFC	CFSWDM3554-E	3,152	WDF	13.96	45	86.5	230/460	2.2	30
		56C	TENV	CFSWDM3554-E	3,048	WDF	15.04	59	86.5	230/460	2.1	30
		145TC	TEFC	CFSWDM3554T-E	3,236	WDF	14.03	48	86.5	230/460	2.2	30
	1200	145TC	TENV	CFSWDM3554T-E	3,132	WDF	15.09	59	86.5	230/460	2.1	30
		182TC	TEFC	CFSWDM3607T-E	3,865	WDF	18.89	90	87.5	230/460	2.6	
2	3600	56C	TEFC	CFSWDM3555-E	3,644	WDF	14.83	50	86.5	230/460	2.5	30
		56C	TENV	CFSWDM3555-E	3,487	WDF	15.04	61	88.5	230/460	2.4	
		143TC	TEFC	CFSWDM3555T-E	3,667	WDF	14.90	50	86.5	230/460	2.5	30
		145TC	TENV	CFSWDM3555T-E	3,563	WDF	15.09	61	88.5	230/460	2.4	
	1800	56C	TEFC	CFSWDM3558-E	3,642	WDF	13.96	45	86.5	230/460	2.7	30
		56C	TENV	CFSWDM3558-E	3,538	WDF	15.04	59	88.5	230/460	2.8	
		143TC	TEFC	CFSWDM3558T-E	3,710	WDF	14.03	45	86.5	230/460	2.7	30
		145TC	TENV	CFSWDM3558T-E	3,606	WDF	15.09	63	88.5	230/460	2.8	
1200	184TC	TEFC	CFSWDM3614T-E	4,290	WDF	18.89	101	88.5	230/460	3.5		
3	3600	56C	TEFC	CFSWDM3559-E	4,136	WDF	16.21	61	86.5	230/460	3.6	
		145TC	TEFC	CFSWDM3559T-E	4,322	WDF	16.28	61	86.5	230/460	3.7	30
		182TC	TENV	CFSWDM3610T-E	4,473	WDF	17.05	96	89.5	230/460	3.5	
	1800	182TC	TEFC	CFSWDM3611T-E	4,454	WDF	18.89	83	89.5	230/460	4.2	30
		182TC	TENV	CFSWDM3611T-E	4,320	WDF	17.05	101	89.5	230/460	4.0	30
1200	213TC	TEFC	CFSWDM3704T-E	5,653	WDF	21.37	158	89.5	230/460	4.5		
5	3600	184TC	TEFC	CFSWDM3613T-E	4,716	WDF	17.39	84	89.5	230/460	5.6	30
	1800	184TC	TEFC	CFSWDM3615T-E	4,751	WDF	18.89	101	89.5	230/460	6.5	30
	1200	213TC	TEFC	CFSWDM3708T-E	6,695	WDF	22.12	179	89.5	230/460	7.4	30
7 1/2	3600	213TC	TEFC	CFSWDM3709T-E	5,916	WDF	19.49	129	91.0	230/460	8.3	30
	1800	213TC	TEFC	CFSWDM3710T-E	6,039	WDF	20.68	170	91.7	230/460	9.5	
	1200	254TC	TEFC	CFSWDM22976T-E	11,494	WDF	24.18	255	91.0	230/460	10.7	30
10	3600	215TC	TEFC	CFSWDM3711T-E	6,708	WDF	20.68	149	91.7	230/460	10.6	30
	1800	215TC	TEFC	CFSWDM3714T-E	7,109	WDF	22.12	187	92.4	230/460	12.5	30

Red catalog number indicates **NEW** product

TOC
 INFO
 SP4
 GP
 SD
 WD
 XP
 PUMP
 HVAC
 FARM
 DP
 UH
 BRM
 VSAC
 IMD
 DCPM
 DCSW
 GRDS
 BUFF
 LATH
 GBPA
 ACPA
 DCPA
 ACC
 MDEX
 INDX
 NOTE

Food Safe stainless steel, three phase, C-face foot mounted, encapsulated

Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
10	1200	256TC	TEFC	CFSWDM23932T-E	13,067	WDF	25.18	290	91.0	230/460	15.1	
15	3600	215TC	TEFC	CFSWDM3713T-E	10,061	WDF	22.12	188	91.7	230/460	17.0	30
		254TC	TEFC	CFSWDM23994T-E	11,653	WDF	24.18	260	91.0	230/460	17.0	
	1800	254TC	TEFC	CFSWDM23933T-E	11,488	WDF	24.18	281	92.4	230/460	17.5	30
20	1200	284TC	TEFC	CFSWDM41900T	14,716	WDF	28.14	488	91.7	230/460	20.0	22
	3600	256TC	TEFC	CFSWDM41906T-E	13,208	WDF	25.18	295	91.0	230/460	23.0	
	1800	256TC	TEFC	CFSWDM23934T-E	13,140	WDF	25.18	290	93.0	230/460	24.0	
25	1200	284TC	TEFC	CFSWDM41902T	18,817	WDF	28.14	493	91.7	230/460	26.0	22
	3600	284TSC	TEFC	CFSWDM41907T	16,897	WDF	26.77	431	91.7	230/460	30.0	22
30	1800	284TC	TEFC	CFSWDM41903T	16,802	WDF	28.14	378	93.6	230/460	30.0	22
	3600	286TSC	TEFC	CFSWDM41908T	19,432	WDF	26.77	445	91.7	230/460	34.0	22
	1800	286TC	TEFC	CFSWDM41904T	19,323	WDF	28.14	395	93.6	230/460	37.0	22
460 volt, Simplified 3-lead connection												
1	3600	56C	TENV	CFSWDM3545-4E	2,920	WDF	11.78	38	82.5	460	1.4	
	1800	56C	TENV	CFSWDM3546-4E	2,950	WDF	12.78	37	85.5	460	1.7	
1 1/2	3600	56C	TENV	CFSWDM3550-4E	3,087	WDF	13.67	50	85.5	460	1.8	
	1800	56C	TENV	CFSWDM3554-4E	3,048	WDF	15.04	59	86.5	460	2.1	
2	3600	145TC	TENV	CFSWDM3555T-4E	3,563	WDF	15.09	61	88.5	460	2.4	
	1800	145TC	TENV	CFSWDM3558T-4E	3,606	WDF	15.09	63	88.5	460	2.8	
3	3600	145TC	TEFC	CFSWDM3559T-4E	4,322	WDF	16.28	61	86.5	460	3.7	
	1800	182TC	TENV	CFSWDM3611T-4E	4,320	WDF	17.05	101	89.5	460	4.0	
5	3600	184TC	TEFC	CFSWDM3613T-4E	4,716	WDF	17.39	81	89.5	460	5.6	
575 volt												
1/2	3600	56C	TENV	CFSWDM3537-5E	2,733	WDF	11.78	35	84.0	575	0.6	
	1800	56C	TENV	CFSWDM3538-5E	2,772	WDF	11.78	35	84.0	575	0.7	
3/4	1800	56C	TENV	CFSWDM3542-5E	2,865	WDF	12.78	41	84.0	575	1.0	
1	1800	56C	TENV	CFSWDM3546-5E	2,991	WDF	12.78	41	85.5	575	1.3	
		143TC	TENV	CFSWDM3546T-5E	3,014	WDF	12.84	43	85.5	575	1.3	
1 1/2	1800	56C	TEFC	CFSWDM3554-5E	3,193	WDF	13.96	45	86.5	575	1.7	
		145TC	TEFC	CFSWDM3554T-5E	3,278	WDF	14.03	45	86.5	575	1.7	
2	1800	56C	TEFC	CFSWDM3558-5E	3,642	WDF	13.96	45	86.5	575	2.3	
		145TC	TEFC	CFSWDM3558T-5E	3,752	WDF	14.03	45	86.5	575	2.3	
3	3600	145TC	TEFC	CFSWDM3559T-5E	4,363	WDF	16.28	61	86.5	575	2.9	
	1800	182TC	TEFC	CFSWDM3611T-5E	4,561	WDF	18.89	86	89.5	575	3.3	
5	3600	184TC	TEFC	CFSWDM3613T-5E	4,822	WDF	17.39	84	89.5	575	4.5	
	1800	184TC	TEFC	CFSWDM3615T-5E	4,857	WDF	18.89	101	89.5	575	5.1	
7 1/2	3600	213TC	TEFC	CFSWDM3709T-5E	5,916	WDF	19.50	131	91.0	575	6.6	
	1800	213TC	TEFC	CFSWDM3710T-5E	6,039	WDF	20.68	139	91.7	575	7.6	
10	3600	215TC	TEFC	CFSWDM3711T-5E	6,708	WDF	20.68	154	90.2	575	9.1	
	1800	215TC	TEFC	CFSWDM3714T-5E	7,109	WDF	22.12	187	92.4	575	10.1	
15	1800	254TC	TEFC	CFSWDM23933T-5E	11,488	WDF	24.18	281	92.4	575	14.2	

Red catalog number indicates **NEW** product

Food Safe stainless steel, three phase, C-face footless, encapsulated



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes	
230/460 volt													
1/2	3600	56C	TENV	VFSWDM3537-E	2,562	WDF	12.96	35	84.0	208-230/460	0.7	30	
	1800	56C	TEFC	VFSFWD3538-E	2,711	WDF	12.96	35	80.0	208-230/460	0.9		
		56C	TENV	VFSWDM3538-E	2,607	WDF	11.78	35	80.0	208-230/460	0.9		
3/4	1200	56C	TENV	VFSWDM3539-E	2,562	WDF	13.96	37	77.0	208-230/460	0.9		
	3600	56C	TENV	VFSWDM3541-E	2,655	WDF	12.96	38	86.5	208-230/460	1.0	30	
		56C	TEFC	VFSFWD3542-E	2,802	WDF	13.96	37	84.0	208-230/460	1.3		
		56C	TENV	VFSWDM3542-E	2,698	WDF	13.96	41	84.0	208-230/460	1.3		
	1	1200	56C	TENV	VFSWDM3543-E	3,246	WDF	14.83	45	82.5	208-230/460	1.3	
		3600	56C	TENV	VFSWDM3545-E	2,792	WDF	12.96	37	82.5	230/460	1.4	30
56C			TEFC	VFSFWD3546-E	2,928	WDF	13.96	44	85.5	230/460	1.7	30	
1800		56C	TENV	VFSWDM3546-E	2,821	WDF	12.78	37	85.5	230/460	1.7	30	
		143TC	TEFC	VFSFWD3546T-E	2,953	WDF	14.03	37	85.5	230/460	1.7	30	
1 1/2	1200	56C	TEFC	VFSWDM3546T-E	2,849	WDF	12.84	37	85.5	230/460	1.7	30	
		56C	TENV	VFSWDM3556-E	3,361	WDF	14.83	45	82.5	230/460	1.7	30	
	3600	56C	TENV	VFSWDM3550-E	2,960	WDF	14.83	53	85.5	230/460	1.8	30	
		143TC	TENV	VFSWDM3550T-E	2,986	WDF	13.72	50	85.5	230/460	1.8	30	
	1800	56C	TEFC	VFSWDM3554-E	3,026	WDF	13.96	45	86.5	230/460	2.2	30	
		56C	TENV	VFSWDM3554-E	2,922	WDF	16.21	59	86.5	230/460	2.1	30	
		145TC	TEFC	VFSWDM3554T-E	3,111	WDF	14.03	45	86.5	230/460	2.2	30	
		145TC	TENV	VFSWDM3554T-E	3,006	WDF	15.09	59	86.5	230/460	2.1	30	
	2	3600	56C	TENV	VFSWDM3555-E	3,362	WDF	16.21	63	88.5	230/460	2.4	
			145TC	TEFC	VFSWDM3555T-E	3,541	WDF	14.90	50	86.5	230/460	2.5	30
145TC			TENV	VFSWDM3555T-E	3,437	WDF	15.09	63	88.5	230/460	2.4		
1800		56C	TEFC	VFSWDM3558-E	3,517	WDF	13.96	56	86.5	230/460	2.7	30	
		56C	TENV	VFSWDM3558-E	3,412	WDF	16.21	63	88.5	230/460	2.8		
		143TC	TEFC	VFSWDM3558T-E	3,586	WDF	14.03	63	86.5	230/460	2.7	30	
3	3600	145TC	TENV	VFSWDM3558T-E	3,480	WDF	15.09	63	88.5	230/460	2.8		
		56C	TEFC	VFSWDM3559-E	4,174	WDF	16.21	61	86.5	230/460	3.7	30	
		145TC	TEFC	VFSWDM3559T-E	4,191	WDF	16.28	63	86.5	230/460	3.7	30	
	1800	182TC	TENV	VFSWDM3610T-E	4,312	WDF	17.05	96	89.5	230/460	3.5		
		56C	TEFC	VFSWDM3651-E	4,271	WDF	17.53	83	89.5	230/460	4.2		
		145TC	TEFC	VFSWDM3651T-E	4,279	WDF	17.60	83	89.5	230/460	4.2		
		182TC	TEFC	VFSWDM3611T-E	4,294	WDF	18.89	86	89.5	230/460	4.2	30	
5	182TC	TENV	VFSWDM3611T-E	4,160	WDF	17.05	101	89.5	230/460	4.0	30		
	3600	184TC	TEFC	VFSWDM3613T-E	4,556	WDF	17.39	81	89.5	230/460	5.6	30	
7 1/2	1800	184TC	TEFC	VFSWDM3615T-E	4,592	WDF	18.89	101	89.5	230/460	6.5	30	
	3600	213TC	TEFC	VFSWDM3709T-E	5,697	WDF	19.49	131	91.0	230/460	8.3	30	
10	1800	213TC	TEFC	VFSWDM3710T-E	5,818	WDF	20.68	136	91.7	230/460	9.5		
	3600	215TC	TEFC	VFSWDM3711T-E	6,490	WDF	20.68	149	91.7	230/460	10.6	30	
15	1800	215TC	TEFC	VFSWDM3714T-E	6,891	WDF	22.12	187	92.4	230/460	12.5	30	
	3600	215TC	TEFC	VFSWDM3713T-E	9,842	WDF	22.12	187	91.7	230/460	17.0	30	

Red catalog number indicates **NEW** product

TOC INFO SP4 GP SD WD XP PUMP HVAC FARM DP UH BRM VSAC IMD DCPM DCSW GRDS BUFF LATH GBPA ACPA DCPA ACC MDEX INDX NOTE

Food Safe stainless steel, three phase, C-face footless, encapsulated

Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
460 volt, Simplified 3-lead connection												
1	3600	56C	TENV	VFSWDM3545-4E	2,792	WDF	12.96	38	82.5	460	1.4	
	1800	56C	TENV	VFSWDM3546-4E	2,821	WDF	12.78	37	85.5	460	1.7	
1 1/2	3600	56C	TENV	VFSWDM3550-4E	2,960	WDF	14.83	50	85.5	460	1.8	
	1800	56C	TENV	VFSWDNM3554-4E	2,922	WDF	16.21	59	86.5	460	2.1	
2	3600	145TC	TENV	VFSWDNM3555T-4E	3,437	WDF	15.09	61	88.5	460	2.4	
	1800	145TC	TENV	VFSWDNM3558T-4E	3,480	WDF	15.09	63	88.5	460	2.8	
3	3600	145TC	TEFC	VFSWDM3559T-4E	4,191	WDF	16.28	61	86.5	460	3.7	
	1800	182TC	TENV	VFSWDNM3611T-4E	4,160	WDF	17.05	101	89.5	460	4.0	
5	3600	184TC	TEFC	VFSWDM3613T-4E	4,556	WDF	17.39	81	89.5	460	5.6	
	1800	184TC	TEFC	VFSWDM3615T-4E	4,592	WDF	18.89	101	89.5	460	6.5	
575 volt												
1/2	1800	56C	TENV	VFSWDM3538-5E	2,607	WDF	12.96	35	84.0	575	0.7	
3/4	1800	56C	TENV	VFSWDM3542-5E	2,698	WDF	13.96	37	84.0	575	1.0	
1	1800	56C	TENV	VFSWDM3546-5E	2,821	WDF	12.78	39	85.5	575	1.3	
		143TC	TENV	VFSWDM3546T-5E	2,849	WDF	12.84	39	85.5	575	1.3	
1 1/2	1800	143TC	TEFC	VFSWDM3554T-5E	3,111	WDF	14.03	48	86.5	575	1.8	
2	1800	143TC	TEFC	VFSWDM3558T-5E	3,586	WDF	14.03	56	86.5	575	2.2	
10	1800	215TC	TEFC	VFSWDM3714T-5E	6,891	WDF	22.12	187	92.4	575	10.1	

Red catalog number indicates **NEW** product

Food Safe stainless steel, three phase, C-face foot mounted, encapsulated, Aegis

Aegis shaft grounding protection ring installed internally for bearing current mitigation



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	1800	56C	TENV	CFSWDM3538-E-G	3,156	WDF	11.78	35	84.0	208-230/460	0.9	
3/4	1800	56C	TENV	CFSWDM3542-E-G	3,249	WDF	12.78	37	84.0	208-230/460	1.3	
1	1800	56C	TENV	CFSWDM3546-E-G	3,375	WDF	12.78	37	85.5	230/460	1.5	30
		143TC	TENV	CFSWDM3546T-E-G	3,398	WDF	12.84	37	85.5	230/460	1.5	30
1 1/2	1800	56C	TENV	CFSWDM3554-E-G	3,473	WDF	15.03	59	86.5	230/460	2.1	30
		145TC	TENV	CFSWDM3554T-E-G	3,557	WDF	15.09	59	86.5	230/460	2.1	30
2	1800	56C	TENV	CFSWDM3558-E-G	3,963	WDF	15.03	63	88.5	230/460	2.8	
		145TC	TENV	CFSWDM3558T-E-G	4,031	WDF	15.09	63	88.5	230/460	2.8	
3	3600	56C	TEFC	CFSWDM3559-E-G	4,561	WDF	16.21	61	86.5	230/460	3.6	
	1800	182TC	TENV	CFSWDM3611T-E-G	4,745	WDF	17.05	101	89.5	230/460	4.0	30
5	1800	184TC	TEFC	CFSWDM3615T-E-G	5,176	WDF	18.89	101	89.5	230/460	6.5	30
7 1/2	1800	213TC	TEFC	CFSWDM3710T-E-G	6,464	WDF	20.68	136	91.7	230/460	9.5	
10	3600	215TC	TEFC	CFSWDM3711T-E-G	7,133	WDF	20.68	154	91.7	230/460	10.6	30
	1800	215TC	TEFC	CFSWDM3714T-E-G	7,534	WDF	22.12	187	92.4	230/460	12.5	30

Red catalog number indicates **NEW** product

TOC
INFO
SP4
GP
SD
WD
XP
PUMP
HVAC
FARM
DP
UH
BRM
VSAC
IMD
DCPM
DCSW
GRDS
BUFF
LATH
GBPA
ACPA
DCPA
ACC
MDEX
INDX
NOTE

Food Safe stainless steel, three phase, C-face footless, encapsulated, Aegis

Aegis shaft grounding protection ring installed internally for bearing current mitigation



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	1800	56C	TENV	VFSWDM3538-E-G	3,032	WDF	11.78	35	84.0	208-230/460	0.9	
3/4	1800	56C	TENV	VFSWDM3542-E-G	3,123	WDF	12.78	37	84.0	208-230/460	1.3	
1	1800	56C	TENV	VFSWDM3546-E-G	3,246	WDF	12.78	37	85.5	230/460	1.5	30
		143TC	TENV	VFSWDM3546T-E-G	3,274	WDF	12.84	37	85.5	230/460	1.5	30
1 1/2	1800	56C	TENV	VFSWDNM3554-E-G	3,347	WDF	15.03	59	86.5	230/460	2.1	30
		145TC	TENV	VFSWDNM3554T-E-G	3,431	WDF	15.09	59	86.5	230/460	2.1	30
2	1800	56C	TENV	VFSWDNM3558-E-G	3,837	WDF	15.03	63	88.5	230/460	2.8	
		145TC	TENV	VFSWDNM3558T-E-G	3,905	WDF	15.09	63	88.5	230/460	2.8	
3	3600	56C	TEFC	VFSWDM3559-E-G	4,599	WDF	16.21	61	86.5	230/460	3.6	30
	1800	145TC	TEFC	VFSWDM3651T-E-G	4,704	WDF	17.59	83	89.5	230/460	4.2	
5	1800	184TC	TEFC	VFSWDM3615T-E-G	5,017	WDF	18.89	101	89.5	230/460	6.5	30

Red catalog number indicates **NEW** product**Food Safe stainless steel, three phase, feather picker, foot mounted, encapsulated**

Cord with water-tight strain relief

For feather picker application found in poultry processing plants



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
3	1800	145T	TEFC	FSWDM3651TP-E	4,899	WDF	16.28	59	81.0	230/460	4.0	2, 8, 31

Food Safe stainless steel, three phase, close-coupled pump foot mounted, encapsulated



Hp	RPM	Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
Mechanical seal, Type JM											
230/460 volt											
1	1800	143JM	JMFSWDM3546T-E	3,440	WDF	14.97	37	85.5	230/460	1.7	30
1 1/2	3600	143JM	JMFSWDM3550T-E	3,578	WDF	15.85	50	85.5	230/460	1.8	30
	1800	145JM	JMFSWDM3554T-E	3,598	WDF	16.15	45	86.5	230/460	2.2	30
2	3600	145JM	JMFSWDM3555T-E	4,075	WDF	17.03	50	86.5	230/460	2.5	30
	1800	145JM	JMFSWDM3558T-E	4,133	WDF	16.15	56	86.5	230/460	2.7	30
3	3600	145JM	JMFSWDM3559T-E	4,895	WDF	18.40	85	86.5	230/460	3.7	30
	1800	182JM	JMFSWDM3611T-E	5,139	WDF	19.72	83	89.5	230/460	4.2	30
5	3600	184JM	JMFSWDM3613T-E	5,535	WDF	18.22	81	89.5	230/460	5.6	30
	1800	184JM	JMFSWDM3615T-E	5,573	WDF	19.72	101	89.5	230/460	6.5	30
7 1/2	3600	213JM	JMFSWDM3709T-E	6,524	WDF	20.62	131	91.0	230/460	8.3	30
	1800	213JM	JMFSWDM3710T-E	6,647	WDF	21.81	139	91.7	230/460	9.5	
10	3600	215JM	JMFSWDM3711T-E	7,315	WDF	21.81	189	91.7	230/460	10.6	30
	1800	215JM	JMFSWDM3714T-E	7,717	WDF	23.56	187	92.4	230/460	12.5	30
15	3600	213JM	JMFSWDM3713T-E	10,588	WDF	23.56	187	91.7	230/460	17.0	30
		254JM	JMFSWDM23994T-E	12,328	WDF	25.68	265	91.0	230/460	17.0	
	1800	254JM	JMFSWDM23933T-E	12,162	WDF	25.68	281	92.4	230/460	17.5	30
20	3600	256JM	JMFSWDM41906T-E	13,882	WDF	26.68	295	91.0	230/460	23.0	
	1800	256JM	JMFSWDM23934T-E	13,814	WDF	26.68	331	93.0	230/460	24.0	

NOTE INDX MDEX ACC DCPA ACPA GBPA LATH BUFF GRDS DCSW DCPM IMD VSAC BRM UH DP FARM HVAC PUMP XP WD SD GP SP4 INFO TOC

Stainless Steel, three phase 1/3 thru 20 Hp

Features

- 300 series stainless steel motor frame, endplates, conduit box, shaft, base, and hardware
- Four condensate drains in each endplate
- Endplate rabbets sealed
- Labyrinth seals on DE and ODE
- 3 year warranty

Applications

- Pumps and wastewater
- Food processing
- Wet environment
- Packaging

IP56

Stainless Steel, three phase, C-face foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes	
230/460 volt													
1/3	3600	56C	TENV	CSSWDM3457	1,736	WDS	11.09	33	74.0	208-230/460	0.6	1, 30	
	1800	56C	TENV	CSSWDM3534	1,826	WDS	11.09	33	75.5	208-230/460	0.7	1, 12, 30	
1/2	3600	56C	TENV	CSSWDM3537	2,050	WDS	11.09	36	70.0	208-230/460	0.9	1, 30	
		56HC	TENV	CSSWDM3537-H	2,050	WDS	11.97	37	72.0	208-230/460	0.8	1	
	1800	56C	TENV	CSSWDM3538	2,200	WDS	11.09	37	78.2	208-230/460	0.9	1, 12, 30	
		56HC	TENV	CSSWDM3538-H	2,200	WDS	11.97	33	80.0	208-230/460	0.9	1	
3/4	1200	56HC	TENV	CSSWDM3539-H	2,373	WDS	11.97	37	78.5	208-230/460	1.0	1	
		56C	TENV	CSSWDM3541	2,119	WDS	11.09	43	80.0	230/460	1.1	1, 12, 30	
	3600	56HC	TENV	CSSWDM3541-H	2,119	WDS	11.97	34	84.0	230/460	1.0	1, 12	
		56C	TENV	CSSWDM3542	2,277	WDS	11.09	42	82.5	208-230/460	1.1	1, 12, 30	
	1800	56HC	TENV	CSSWDM3542-H	2,277	WDS	11.97	34	82.5	208-230/460	1.1	1, 12	
		56C	TENV	CSSWDM3543-H	2,575	WDS	11.97	51	82.5	230/460	1.4	1, 12	
1	3600	56C	TENV	CESSWDM3545	2,323	WDS	11.09	39	82.5	230/460	1.4	12	
		56HC	TENV	CESSWDM3545-H	2,323	WDS	11.97	38	84.0	230/460	1.3	12	
	56C	TENV	CESSWDM3546	2,314	WDS	11.09	41	85.5	230/460	1.7	1, 30		
		56HC	TENV	CESSWDM3546-H	2,314	WDS	11.97	41	87.5	230/460	1.5		
	1800	143TC	TEFC	CESSWDM3546T	2,348	WDS	13.42	52	85.5	230/460	1.7	1, 30	
		56HC	TENV	CESSWDM3556-H	2,620	WDS	14.22	64	84.0	230/460	1.7	1, 30	
	11/2	3600	56C	TENV	CESSWDM3550	2,337	WDS	12.96	56	85.5	230/460	1.8	1, 30
			56HC	TENV	CESSWDM3550-H	2,337	WDS	12.85	50	85.5	230/460	1.8	1, 30
143TC			TENV	CESSWDM3550T	2,356	WDS	13.23	60	85.5	230/460	1.8	1, 30	
1800		56C	TEFC	CESSWDM3554	2,358	WDS	13.34	41	86.5	230/460	2.3	1, 30	
		56HC	TEFC	CESSWDM3554-H	2,358	WDS	13.03	45	86.5	230/460	2.2	1, 30	
		145TC	TEFC	CESSWDM3554T	2,393	WDS	13.42	55	86.5	230/460	2.3	1, 30	
2	3600	56HC	TENV	CESSWDM3555-H	3,114	WDS	12.85	61	86.5	230/460	2.5		
		145TC	TEFC	CESSWDM3555T	2,855	WDS	14.30	60	86.5	208-230/460	2.5	1, 30	

Red catalog number indicates **NEW** product

Stainless Steel, three phase, C-face foot mounted

Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
2	1800	56C	TEFC	CESSWDM3558	2,841	WDS	13.34	45	86.5	230/460	2.7	8, 30
		56HC	TEFC	CESSWDM3558-H	2,841	WDS	13.03	45	86.5	230/460	2.7	
		143TC	TEFC	CESSWDM3558T	2,875	WDS	13.42	45	86.5	230/460	2.7	8, 30
3	3600	145TC	TEFC	CESSWDM3559T	3,440	WDS	15.67	74	86.5	208-230/460	3.7	1, 30
		182TC	TEFC	CESSWDM3610T	3,674	WDS	16.82	90	88.5	230/460	3.7	1, 30
5	1800	182TC	TEFC	CESSWDM3611T	3,361	WDS	18.32	102	89.5	230/460	4.2	1, 30
		182TC	TEFC	CESSWDM3613T	3,909	WDS	18.32	106	89.5	230/460	5.7	30
7 1/2	3600	184TC	TEFC	CESSWDM3615T	3,782	WDS	18.32	112	89.5	230/460	6.5	
		213TC	TEFC	CESSWDM3709T	4,588	WDS	18.94	166	91.0	230/460	8.3	1, 30
10	1800	213TC	TEFC	CESSWDM3710T	4,731	WDS	20.07	137	91.7	230/460	9.5	1
		215TC	TEFC	CESSWDM3711T	5,119	WDS	20.07	184	91.7	230/460	10.6	1, 30
15	3600	215TC	TEFC	CESSWDM3714T	5,218	WDS	21.57	190	92.4	230/460	12.5	1, 30
		215TC	TEFC	CESSWDM3713T	7,682	WDS	21.57	187	91.7	230/460	17.0	8, 30
20	1800	254TC	TEFC	CESSWDM23994T	10,448	WDS	24.67	293	91.0	230/460	16.5	1, 30
		254TC	TEFC	CESSWDM23933T	10,283	WDS	24.67	293	92.4	230/460	17.5	1, 30
20	3600	256TC	TEFC	CESSWDM41906T	11,993	WDS	24.67	312	91.0	230/460	21.5	2
		256TC	TEFC	CESSWDM23934T	11,925	WDS	24.67	299	93.0	230/460	24.0	8
575 volt												
1/2	1800	56C	TENV	CSSWDM3538-5	2,200	WDS	11.09	37	80.0	575	0.8	1, 12
3/4	1800	56C	TENV	CSSWDM3542-5	2,277	WDS	11.09	41	82.5	575	0.9	1, 12
1	1800	56C	TENV	CESSWDM3546-5	2,314	WDS	11.09	46	85.5	575	1.2	
		143TC	TEFC	CESSWDM3546T-5	2,348	WDS	13.42	51	87.5	575	1.3	1
1 1/2	3600	56C	TENV	CESSWDM3550-5	2,337	WDS	12.96	50	85.5	575	1.5	
		145TC	TEFC	CESSWDM3554T-5	2,393	WDS	13.42	56	87.5	575	1.7	1
2	1800	145TC	TENV	CESSWDM3555T-5	2,855	WDS	14.60	61	88.5	575	1.9	8
		145TC	TEFC	CESSWDM3558T-5	2,875	WDS	13.42	64	86.5	575	2.3	8
3	3600	145TC	TEFC	CESSWDM3559T-5	3,440	WDS	15.67	73	86.5	575	2.9	1
		182TC	TENV	CESSWDM3610T-5	3,674	WDS	19.82	96	89.5	575	2.8	8
	1800	182TC	TEFC	CESSWDM3611T-5	3,361	WDS	16.82	92	89.5	575	3.2	1
		182TC	TENV	CESSWDM3611T-5	3,361	WDS	19.82	101	89.5	575	3.2	8
5	3600	184TC	TEFC	CESSWDM3613T-5	3,909	WDS	18.32	106	90.2	575	4.6	
		184TC	TEFC	CESSWDM3615T-5	3,782	WDS	18.32	112	89.5	575	5.2	
7 1/2	3600	213TC	TEFC	CESSWDM3709T-5	4,588	WDS	19.03	129	91.0	575	6.7	
		213TC	TEFC	CESSWDM3710T-5	4,731	WDS	20.07	139	91.7	575	7.6	
10	3600	215TC	TEFC	CESSWDM3711T-5	5,119	WDS	20.16	154	91.7	575	8.5	1
		215TC	TEFC	CESSWDM3714T-5	5,218	WDS	21.57	185	91.7	575	9.8	1
15	1800	254TC	TEFC	CESSWDM23933T-5	10,283	WDS	24.67	281	92.4	575	14.2	

Red catalog number indicates **NEW** product

TOC INFO SP4 GP SD WD XP PUMP FARM HVAC DP UH BRM VSAC IMD DCPM DCSW DCSW GRDS BUFF LATH GBPA ACBA ACC DCPA MDEX INDX

Stainless Steel, three phase, C-face footless



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/3	3600	56C	TENV	VSSWDM3457	1,685	WDS	11.09	33	74.0	208-230/460	0.6	1, 10, 30
	1800	56C	TENV	VSSWDM3534	1,775	WDS	11.09	35	75.5	208-230/460	0.9	1, 10, 12, 30
1/2	3600	56C	TENV	VSSWDM3537	2,001	WDS	11.09	37	70.0	208-230/460	0.9	2, 10, 30
	1800	56C	TEFC	VSSFWDM3538	2,277	WDS	12.34	40	78.2	208-230/460	0.9	1, 10, 12, 30
		56C	TENV	VSSWDM3538	2,154	WDS	11.09	40	78.2	230/460	0.9	1, 10, 12, 30
3/4	3600	56C	TENV	VSSWDM3541	2,078	WDS	11.09	41	80.0	230/460	1.1	1, 10, 12, 30
	1800	56C	TEFC	VSSFWDM3542	2,351	WDS	12.34	44	82.5	208-230/460	1.1	1, 10
		56C	TENV	VSSWDM3542	2,233	WDS	11.09	42	82.5	208-230/460	1.1	1, 10
1	1800	56C	TEFC	VESSFWDM3546	2,485	WDS	12.34	39	85.5	230/460	1.6	
		56C	TENV	VESSWDM3546	2,254	WDS	12.09	44	85.5	230/460	1.7	1, 30
		143TC	TEFC	VESSWDM3546T	2,289	WDS	13.42	44	87.5	230/460	1.5	1, 30
1 1/2	1800	56C	TEFC	VESSWDM3554	2,299	WDS	13.34	46	86.5	230/460	2.3	1, 30
		145TC	TEFC	VESSWDM3554T	2,333	WDS	13.42	45	86.5	230/460	2.3	1, 30
2	1800	56C	TEFC	VESSWDM3558	2,781	WDS	13.34	48	86.5	230/460	2.7	8, 30
		145TC	TEFC	VESSWDM3558T	2,816	WDS	13.42	45	86.5	230/460	2.7	8, 30
3	3600	145TC	TEFC	VESSWDM3559T	3,346	WDS	15.67	64	86.5	208-230/460	3.7	1, 30
	1800	182TC	TEFC	VESSWDM3611T	3,213	WDS	18.25	60	89.5	230/460	4.2	1, 30
5	3600	184TC	TEFC	VESSWDM3613T	3,761	WDS	18.25	83	90.2	230/460	5.7	30
	1800	184TC	TEFC	VESSWDM3615T	3,634	WDS	18.25	101	89.5	230/460	6.5	30
7 1/2	1800	213TC	TEFC	VESSWDM3710T	4,601	WDS	20.07	139	91.7	230/460	9.5	1
10	1800	215TC	TEFC	VESSWDM3714T	5,088	WDS	21.57	188	92.4	230/460	12.5	1, 30
575 volt												
1	1800	56C	TENV	VESSWDM3546-5	2,254	WDS	12.09	39	85.5	575	1.2	
1 1/2	1800	145TC	TEFC	VESSWDM3554T-5	2,333	WDS	13.41	45	87.5	575	1.7	1
2	3600	56C	TEFC	VESSWDM3555-5	2,725	WDS	14.22	41	86.5	575	2.0	1
	1800	145TC	TEFC	VESSWDM3558T-5	2,816	WDS	15.66	56	88.5	575	2.2	8
3	1800	182TC	TEFC	VESSWDM3611T-5	3,213	WDS	18.25	83	89.5	575	3.3	1
5	1800	184TC	TEFC	VESSWDM3615T-5	3,634	WDS	18.25	112	89.5	575	5.1	1
10	1800	215TC	TEFC	VESSWDM3714T-5	5,088	WDS	21.57	191	92.4	575	10.1	1

Red catalog number indicates **NEW** product

Paint Free, three phase 1/2 thru 10 Hp

Features

- 300 series stainless steel motor frame, endplates, conduit box, shaft, base, and hardware
- Sealed ball bearings
- Rotating non-contact labyrinth seal
- No exterior paint
- 3 year warranty

Applications

- Food processing
- Outdoor applications
- Packaging

IP55

Paint-Free, three phase, C-face foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	3600	56C	TENV	CSWDM3537	1,204	WDP	11.06	29	70.0	208-230/460	0.9	2, 30
	1800	56C	TENV	CSWDM3538	1,177	WDP	11.06	27	78.2	230/460	0.9	1, 12, 30
	1200	56C	TENV	CSWDM3539	1,647	WDP	12.06	38	78.5	208-230/460	1.0	1, 12, 30
3/4	3600	56C	TENV	CSWDM3541	1,263	WDP	11.06	36	80.0	208-230/460	1.1	1, 12, 30
	1800	56C	TENV	CSWDM3542	1,359	WDP	11.06	30	82.5	230/460	1.1	1, 12, 30
	1200	56C	TENV	CSWDM3543	1,988	WDP	12.93	47	81.5	208-230/460	1.4	30
1	1800	56C	TENV	CESWDM3546	1,894	WDP	12.06	40	85.5	230/460	1.7	1, 30
		143TC	TENV	CESWDM3546T	1,853	WDP	12.12	39	87.5	230/460	1.5	1, 30
1 1/2	1800	56C	TENV	CESWDM3554	1,933	WDP	12.93	50	86.5	230/460	2.3	30
		145TC	TENV	CESWDM3554T	1,984	WDP	12.99	50	86.5	230/460	2.3	30
2	3600	145TC	TEFC	CESWDM3555T	2,350	WDP	14.16	52	86.5	208-230/460	2.5	1, 30
		56C	TEFC	CESWDM3558	2,287	WDP	13.22	45	86.5	230/460	2.9	1, 30
		145TC	TEFC	CESWDM3558T	2,435	WDP	15.54	56	88.5	230/460	2.8	1, 30
3	3600	143TC	TEFC	CESWDM3559T	2,892	WDP	15.54	62	86.5	208-230/460	3.7	1, 30
		1800	182TC	TEFC	CESWDM3611T	2,979	WDP	16.50	79	89.5	230/460	4.0
5	3600	184TC	TEFC	CESWDM3613T	3,667	WDP	18.00	88	90.2	230/460	5.7	30
		1800	184TC	TEFC	CESWDM3615T	3,466	WDP	18.00	92	89.5	230/460	6.7
7 1/2	3600	213TC	TEFC	CESWDM3709T	4,629	WDP	18.68	134	91.0	230/460	8.3	1, 30
		1800	213TC	TEFC	CESWDM3710T	4,265	WDP	19.81	135	91.7	230/460	9.5
10	3600	215TC	TEFC	CESWDM3711T	5,131	WDP	19.81	154	91.7	230/460	10.6	1, 30
		1800	215TC	TEFC	CESWDM3714T	4,853	WDP	21.31	165	91.7	230/460	12.5
575 volt												
1/2	3600	56C	TENV	CSWDM3537-5	1,204	WDP	11.06	37	70.0	575	0.7	2, 10
	1800	56C	TENV	CSWDM3538-5	1,177	WDP	11.06	33	80.0	575	0.7	1, 10, 12
3/4	3600	56C	TENV	CSWDM3541-5	1,263	WDP	11.06	39	80.0	575	0.9	10, 12
	1800	56C	TENV	CSWDM3542-5	1,359	WDP	11.06	30	78.5	575	1.1	1, 10, 12

Red catalog number indicates **NEW** product

Paint-Free, three phase, C-face foot mounted

Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
575 volt												
1	1800	56C	TENV	CESWDM3546-5	1,894	WDP	12.06	39	85.5	575	1.2	10
		143TC	TENV	CESWDM3546T-5	1,853	WDP	12.12	39	85.5	575	1.2	10
1 1/2	1800	56C	TENV	CESWDM3554-5	1,933	WDP	12.94	47	86.5	575	1.7	10
		145TC	TENV	CESWDM3554T-5	1,984	WDP	12.99	47	86.5	575	1.7	10
2	1800	56C	TENV	CESWDM3558-5	2,287	WDP	14.31	56	88.5	575	2.1	10

Red catalog number indicates **NEW** product

Paint-Free, three phase, C-face footless


Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	1800	56C	TENV	VSWDM3538	1,164	WDP	11.06	28	78.2	230/460	0.9	1, 12, 30
3/4	1800	56C	TENV	VSWDM3542	1,347	WDP	11.06	31	82.5	230/460	1.1	1, 12, 30
1	1800	56C	TENV	VESWDM3546	1,803	WDP	12.06	39	85.5	230/460	1.7	1, 30
		143TC	TENV	VESWDM3546T	1,810	WDP	12.12	43	87.5	230/460	1.5	1, 30
1 1/2	1800	56C	TENV	VESWDM3554	1,963	WDP	12.93	47	86.5	230/460	2.3	30
		145TC	TENV	VESWDM3554T	1,963	WDP	12.99	49	86.5	230/460	2.3	30
2	1800	145TC	TEFC	VESWDM3558T	2,241	WDP	15.54	55	88.5	230/460	2.8	1, 30
575 volt												
1/2	1800	56C	TENV	VSWDM3538-5	1,164	WDP	11.06	33	80.0	575	0.7	1, 10, 12
3/4	1800	56C	TENV	VSWDM3542-5	1,347	WDP	11.06	37	78.5	575	1.1	1, 10, 12
1	1800	56C	TENV	VESWDM3546-5	1,803	WDP	12.06	39	85.5	575	1.2	10
		143TC	TENV	VESWDM3546T-5	1,810	WDP	12.12	39	85.5	575	1.2	10
1 1/2	1800	56C	TENV	VESWDM3554-5	1,963	WDP	12.95	57	86.5	575	1.7	10
		145TC	TENV	VESWDM3554T-5	1,963	WDP	12.99	47	86.5	575	1.7	10
2	1800	145TC	TENV	VESWDM3558T-5	2,235	WDP	14.38	62	88.5	575	2.1	10

Red catalog number indicates **NEW** product

Paint-Free, three phase, C-face foot mounted, Inverter Duty

Class H insulation
Not encoder adaptable



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	1800	56C	TENV	IDCSWDM3538	2,554	WDP	11.06	31	78.2	208-230/460	0.9	30
3/4	1800	56C	TENV	IDCSWDM3542	2,892	WDP	11.06	32	82.5	208-230/460	1.2	30
1	1800	56C	TENV	IDCSWDM3546	3,002	WDP	12.06	40	85.5	208-230/460	1.5	30
		143TC	TENV	IDCSWDM3546T	3,002	WDP	12.12	42	85.5	230/460	1.7	
1 1/2	1800	56C	TEFC	IDCSWDM3554	3,211	WDP	13.24	51	86.5	230/460	2.3	
		145TC	TEFC	IDCSWDM3554T	3,211	WDP	13.29	49	86.5	230/460	2.3	
2	1800	56C	TEFC	IDCSWDM3558	3,430	WDP	13.22	44	86.5	230/460	2.9	
		145TC	TEFC	IDCSWDM3558T	3,430	WDP	13.29	48	86.5	230/460	2.9	
3	1800	182TC	TEFC	IDCSWDM3611T	3,761	WDP	18.00	85	89.5	230/460	4.2	
5	1800	184TC	TEFC	IDCSWDM3615T	4,377	WDP	18.00	99	89.5	230/460	6.5	
7 1/2	1800	213TC	TEFC	IDCSWDM3710T	6,626	WDP	19.81	136	91.7	230/460	9.5	
10	1800	215TC	TEFC	IDCSWDM3714T	7,576	WDP	21.31	187	92.4	230/460	12.5	

Paint-Free, three phase, C-face footless, Inverter Duty

Class H insulation
Not encoder adaptable



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	1800	56C	TENV	IDVSWDM3538	2,533	WDP	11.06	32	78.2	230/460	0.9	
3/4	1800	56C	TENV	IDVSWDM3542	2,878	WDP	11.06	35	82.5	230/460	1.1	
1	1800	56C	TENV	IDVSWDM3546	2,987	WDP	12.06	40	85.5	230/460	1.7	
		143TC	TENV	IDVSWDM3546T	2,987	WDP	12.12	40	85.5	230/460	1.7	
1 1/2	1800	56C	TEFC	IDVSWDM3554	3,195	WDP	13.22	50	86.5	230/460	2.3	
		145TC	TEFC	IDVSWDM3554T	3,195	WDP	13.29	50	86.5	230/460	2.3	
2	1800	56C	TEFC	IDVSWDM3558	3,402	WDP	13.22	45	86.5	230/460	2.9	
		145TC	TEFC	IDVSWDM3558T	3,402	WDP	13.29	46	86.5	230/460	2.9	
3	1800	182TC	TEFC	IDVSWDM3611T	3,577	WDP	18.00	80	89.5	230/460	4.2	
5	1800	184TC	TEFC	IDVSWDM3615T	4,169	WDP	18.00	97	89.5	230/460	6.5	

TOC
INFO
SP4
GP
SD
WD
XP
PUMP
HVAC
FARM
DP
UH
BRM
VSAC
IND
DCPM
DCSW
DCSW
GRDS
BUFF
LATH
GBPA
ACPA
DCPA
ACC
MDEX
INDEX
NOTE

White Washdown, single phase

1/2 thru 1 1/2 Hp

Features

- 300 series stainless steel hardware
- Neoprene gaskets
- Double sealed ball bearings
- Lip and V-Ring seal on DE
- White epoxy, corrosion resistant finish
- Stainless steel shaft extension

Applications

- Packaging
- Food processing
- Pumps and wastewater
- Wet environment

IP55

White Washdown, single phase, foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
115/230 volt												
1/2	1800	56	TEFC	WDL3504	1,024	WDW	12.23	34	66.0	115/230	3.5	1, 12, 30
3/4	1800	56	TEFC	WDL3507	1,199	WDW	13.22	37	70.0	115/230	5.0	1, 12, 30
1	1800	56	TEFC	WDL3510	1,386	WDW	13.23	41	68.0	115/230	6.2	1, 30
1 1/2	1800	145T	TEFC	WDL3514T	1,708	WDW	14.18	50	80.0	115/230	6.2	1, 30

White Washdown, single phase, C-face foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
115/230 volt												
1/2	1800	56C	TEFC	CWDL3504	1,072	WDW	12.23	35	66.0	115/230	3.5	1, 12, 30
3/4	1800	56C	TEFC	CWDL3507	1,248	WDW	13.22	36	70.0	115/230	5.0	1, 12, 30
1	3600	56C	TEFC	CWDL3509	1,169	WDW	12.22	37	68.0	115/230	5.9	1, 12, 30
	1800	56C	TEFC	CWDL3510	1,434	WDW	13.23	41	68.0	115/230	6.2	1, 30
1 1/2	3600	56C	TEFC	CWDL3513	1,444	WDW	13.22	41	70.0	115/230	8.0	1, 30
	1800	56C	TEFC	CWDL3514	1,717	WDW	14.12	50	80.0	115/230	6.1	1, 30

White Washdown, single phase, C-face footless



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
115/230 volt												
1/2	1800	56C	TEFC	VWDL3504	1,028	WDW	12.25	35	66.0	115/230	3.5	1, 12, 30
3/4	1800	56C	TEFC	VWDL3507	1,207	WDW	13.22	36	70.0	115/230	5.0	1, 12, 30
1	1800	56C	TEFC	VWDL3510	1,382	WDW	13.25	42	68.0	115/230	6.2	1, 30
1 1/2	1800	56C	TEFC	VWDL3514	1,658	WDW	14.10	48	80.0	115/230	6.1	1, 30

White Washdown, three phase

1/2 thru 20 Hp

Features

- 300 series stainless steel hardware
- Neoprene gaskets
- Double sealed ball bearings
- Lip and V-Ring seal on DE
- White epoxy, corrosion resistant finish
- Stainless steel shaft extension
- 3 year warranty, NEMA Premium® efficiency

Applications

- Packaging
- Food processing
- Pumps and wastewater
- Wet environment

IP55

White Washdown, three phase, foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/2	1800	56	TENV	WDM3538	1,023	WDW	11.06	27	78.2	230/460	0.9	1, 12, 30
3/4	1800	56	TENV	WDM3542	1,093	WDW	11.06	30	82.5	230/460	1.1	1, 12, 30
1	3600	143T	TENV	EWDM3545T	1,447	WDW	11.12	35	82.5	230/460	1.3	1
	1800	56	TENV	EWDM3546	1,490	WDW	12.06	39	85.5	230/460	1.7	1, 30
		143T	TENV	EWDM3546T	1,526	WDW	12.12	39	85.5	230/460	1.7	1, 30
	1200	145T	TEFC	EWDM3556T	1,754	WDW	13.29	41	82.5	230/460	1.8	1
	900	182T	TEFC	EWDM3617T	2,890	WDW	16.54	65	75.5	230/460	2.3	1
1 1/2	3600	143T	TENV	EWDM3550T	1,495	WDW	12.12	48	85.5	230/460	2.0	
	1800	145T	TENV	EWDM3554T	1,678	WDW	12.99	49	86.5	230/460	2.3	30
	1200	182T	TEFC	EWDM3607T	1,940	WDW	16.54	91	87.5	230/460	2.4	1
	900	184T	TEFC	EWDM3618T	3,395	WDW	18.04	95	78.5	230/460	3.0	1
2	3600	145T	TEFC	EWDM3555T	1,885	WDW	14.17	50	86.5	230/460	2.5	1
	1800	143T	TEFC	EWDM3558T	1,969	WDW	13.29	46	86.5	230/460	2.8	1, 30
	1200	184T	TEFC	EWDM3614T	2,174	WDW	18.04	100	88.5	230/460	3.5	1
	900	213T	TEFC	EWDM3702T	4,746	WDW	19.02	111	85.5	230/460	3.5	1
3	3600	182T	TEFC	EWDM3610T	2,053	WDW	15.17	50	86.5	230/460	3.6	1
	1800	182T	TEFC	EWDM3611T	2,458	WDW	16.54	73	89.5	230/460	4.2	1, 30
	1200	213T	TEFC	EWDM3704T	2,819	WDW	19.02	139	89.5	230/460	4.6	1
5	900	215T	TEFC	EWDM3705T	5,243	WDW	19.04	111	86.5	230/460	5.2	1
	3600	184T	TEFC	EWDM3613T	2,962	WDW	16.54	74	88.5	230/460	5.9	1
	1800	184T	TEFC	EWDM3615T	2,798	WDW	18.04	90	89.5	230/460	6.7	1, 30
7 1/2	1200	215T	TEFC	EWDM3708T	3,188	WDW	20.52	185	89.5	230/460	7.2	1
	3600	213T	TEFC	EWDM3709T	4,146	WDW	17.89	129	89.5	230/460	9.0	1
	1800	213T	TEFC	EWDM3710T	3,502	WDW	19.04	129	91.7	230/460	9.5	1, 30
10	1200	254T	TEFC	EWDM22976T	6,050	WDW	23.57	265	91.0	230/460	10.7	1
10	3600	215T	TEFC	EWDM3711T	4,387	WDW	17.89	123	90.2	230/460	11.6	1

Red catalog number indicates **NEW** product

White Washdown, three phase, foot mounted

Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
10	1800	215T	TEFC	EWDM3714T	3,815	WDW	20.54	165	91.7	230/460	12.5	1
	1200	256T	TEFC	EWDM23932T	6,939	WDW	23.57	276	91.0	230/460	14.7	30
15	3600	254T	TEFC	EWDM23994T	8,365	WDW	22.32	169	91.0	230/460	15.3	1
	1800	254T	TEFC	EWDM23933T	8,228	WDW	23.57	248	92.4	230/460	18.0	1, 30
20	3600	256T	TEFC	EWDM41906T	9,643	WDW	23.57	242	91.0	230/460	23.0	
	1800	256T	TEFC	EWDM23934T	9,589	WDW	23.57	269	93.0	230/460	24.0	1, 30

Red catalog number indicates **NEW** product

TOC
INFO
SP4
GP
SD
WD
XP
PUMP
HVAC
FARM
DP
UH
BRM
VSAC
IMD
DCPM
DCSW
GRDS
BUFF
LATH
GBPA
ACPA
DCPA
ACC
MDEX
INDX
NOTE

White Washdown, three phase, C-face foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes	
230/460 volt													
1/3	1800	56C	TENV	CWDM3534	891	WDW	11.06	33	75.5	208-230/460	0.9	1	
		56C	TENV	CWDM3537	995	WDW	11.06	29	70.0	208-230/460	0.9	1, 12	
	3600	56HC	TENV	CWDM3537-H	995	WDW	11.91	37	70.0	208-230/460	0.9	1, 12	
1/2	1800	56C	TENV	CWDM3538	1,077	WDW	11.06	28	78.2	230/460	0.9	1, 12, 30	
		56HC	TENV	CWDM3538-H	1,077	WDW	11.91	33	80.0	208-230/460	0.9	1, 12	
	1200	56C	TENV	CWDM3539	1,360	WDW	12.06	37	78.5	208-230/460	1.0	1, 12	
		56HC	TENV	CWDM3539-H	1,360	WDW	11.91	37	78.5	208-230/460	1.0	1, 12	
	3/4	3600	56C	TENV	CWDM3541	1,042	WDW	11.06	35	80.0	230/460	1.1	1, 12, 30
			56HC	TENV	CWDM3541-H	1,042	WDW	11.91	34	80.0	230/460	1.1	1, 12
1800		56C	TENV	CWDM3542	1,167	WDW	11.07	29	82.5	230/460	1.1	1, 12, 30	
		56H	TENV	CWDM3542-H	1,167	WDW	11.91	30	82.5	208-230/460	1.2	1, 12, 30	
1200		56C	TENV	CWDM3543	1,642	WDW	12.94	46	80.0	208-230/460	1.4	1	
		56HC	TENV	CWDM3543-H	1,642	WDW	12.78	45	81.5	208-230/460	1.4		
1	3600	56C	TEFC	CEWDM3545	1,711	WDW	12.22	33	77.0	230/460	1.4	1, 12	
		56C	TENV	CEWDM3545	1,615	WDW	11.06	35	82.5	230/460	1.3		
		56HC	TENV	CEWDM3545-H	1,615	WDW	11.91	35	82.5	230/460	1.3	1, 12, 30	
		143TC	TENV	CEWDM3545T	1,675	WDW	12.12	35	82.5	230/460	1.3	1	
		56C	TENV	CEWDM3546	1,719	WDW	12.05	41	85.5	230/460	1.7	30	
	1800	56HC	TENV	CEWDM3546-H	1,719	WDW	11.91	39	85.5	230/460	1.7	1, 30	
		143TC	TENV	CEWDM3546T	1,754	WDW	12.13	37	85.5	230/460	1.7	30	
		56C	TEFC	CEWDM3556	1,930	WDW	13.22	43	82.5	230/460	1.8	1, 30	
	1200	56HC	TEFC	CEWDM3556-H	1,930	WDW	13.08	41	82.5	230/460	1.8	1	
		145TC	TEFC	CEWDM3556T	1,981	WDW	13.28	41	82.5	230/460	1.8	1	
		900	182TC	TEFC	CEWDM3617T	3,089	WDW	16.54	65	75.5	230/460	2.3	1, 30
	1 1/2	3600	56C	TENV	CEWDM3550	1,759	WDW	12.06	46	85.5	230/460	2.0	1, 30
			56HC	TENV	CEWDM3550-H	1,759	WDW	11.91	48	85.5	230/460	2.0	1
			143TC	TENV	CEWDM3550T	1,797	WDW	12.12	48	85.5	230/460	2.0	1
		1800	56C	TENV	CEWDM3554	1,798	WDW	15.05	50	86.5	230/460	2.3	30
56HC			TENV	CEWDM3554-H	1,798	WDW	12.78	56	86.5	230/460	2.1		
145TC			TENV	CEWDM3554T	1,836	WDW	13.00	48	86.5	230/460	2.3	30	
1200		182TC	TEFC	CEWDM3607T	2,139	WDW	16.54	72	87.5	230/460	2.4	1, 30	
900		184TC	TEFC	CEWDM3618T	3,595	WDW	18.04	101	78.5	230/460	3.0	1	
2		3600	56HC	TEFC	CEWDM3555-H	1,902	WDW	13.08	41	85.5	230/460	2.5	1
	56HCY		TEFC	CEWDM3555	1,902	WDW	13.23	35	85.5	230/460	2.5	1, 30	
	145TC		TEFC	CEWDM3555T	1,940	WDW	13.29	45	85.5	230/460	2.5	1, 30	
	1800	56C	TEFC	CEWDM3558	1,961	WDW	13.22	48	86.5	230/460	2.8	1, 30	
		56HC	TEFC	CEWDM3558-H	1,961	WDW	13.08	48	86.5	230/460	2.8	1, 30	
		145TC	TEFC	CEWDM3558T	2,024	WDW	13.28	46	86.5	230/460	2.8	1, 30	
		145TC	TENV	CEWDM3558T	1,976	WDW	14.37	54	86.5	230/460	2.7	1, 30	
	1200	184TC	TEFC	CEWDM3614T	2,373	WDW	18.04	93	88.5	230/460	3.5	1, 30	
	900	213TC	TEFC	CEWDM3702T	5,054	WDW	19.76	111	85.5	230/460	3.5	1	

Red catalog number indicates **NEW** product

White Washdown, three phase, C-face foot mounted

Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
3	3600	145TC	TEFC	CEWDM3559T	2,389	WDW	14.17	60	86.5	230/460	3.6	1, 30
		182TC	TEFC	CEWDM3610T	2,253	WDW	15.18	57	86.5	230/460	3.6	1, 30
	1800	182TC	TEFC	CEWDM3611T	2,658	WDW	16.54	78	89.5	230/460	4.2	1, 30
	1200	213TC	TEFC	CEWDM3704T	3,127	WDW	19.78	136	89.5	230/460	4.6	1, 30
	900	215TC	TEFC	CEWDM3705T	5,758	WDW	19.76	111	86.5	230/460	5.2	1
5	3600	184TC	TEFC	CEWDM3613T	3,162	WDW	16.54	80	88.5	230/460	5.8	1, 30
	1800	184TC	TEFC	CEWDM3615T	3,012	WDW	18.04	96	89.5	230/460	6.7	1, 30
	1200	215TC	TEFC	CEWDM3708T	3,703	WDW	21.27	185	89.5	230/460	7.2	1, 30
7 1/2	3600	184TC	TEFC	CEWDM3616T	3,758	WDW	18.04	101	89.5	230/460	8.4	1, 30
		213TC	TEFC	CEWDM3709T	4,454	WDW	18.64	143	89.5	230/460	9.0	1, 30
	1800	213TC	TEFC	CEWDM3710T	3,810	WDW	19.78	151	91.7	230/460	9.5	1, 30
10	1200	254TC	TEFC	CEWDM22976T	6,358	WDW	23.56	280	91.0	230/460	11.0	1, 30
		215TC	TEFC	CEWDM3711T	4,902	WDW	18.64	122	90.2	230/460	11.6	1, 30
		215TC	TEFC	CEWDM3714T	4,331	WDW	21.27	165	91.7	230/460	12.5	1
15	1200	256TC	TEFC	CEWDM23932T	7,227	WDW	23.56	289	91.0	230/460	15.1	30
		215TC	TEFC	CEWDM3713T	6,160	WDW	21.26	174	91.0	230/460	17.0	1, 30
		254TC	TEFC	CEWDM23994T	8,653	WDW	21.89	188	91.0	230/460	16.6	1, 30
20	1800	254TC	TEFC	CEWDM23933T	8,517	WDW	23.56	256	92.4	230/460	18.0	1, 30
		256TC	TEFC	CEWDM41906T	9,931	WDW	23.56	274	91.0	230/460	23.0	1
		256TC	TEFC	CEWDM23934T	9,877	WDW	23.56	283	93.0	230/460	24.0	1, 30
575 volt												
1/2	1800	56C	TENV	CWDM3538-5	1,077	WDW	11.07	26	80.0	575	0.8	1, 12
3/4	1800	56C	TENV	CWDM3542-5	1,167	WDW	11.06	35	82.5	575	0.9	1, 12
1	1800	56C	TENV	CEWDM3546-5	1,719	WDW	12.06	39	85.5	575	1.3	
		143TC	TENV	CEWDM3546T-5	1,754	WDW	12.12	38	85.5	575	1.3	
1 1/2	1800	145TC	TENV	CEWDM3554T-5	1,836	WDW	13.00	46	86.5	575	1.7	1
2	1800	145TC	TEFC	CEWDM3558T-5	2,024	WDW	13.28	46	86.5	575	2.2	1
3	3600	145TC	TEFC	CEWDM3559T-5	2,389	WDW	14.17	52	86.5	575	2.9	1
		182TC	TEFC	CEWDM3611T-5	2,658	WDW	16.54	77	89.5	575	3.3	1
5	3600	184TC	TEFC	CEWDM3613T-5	3,162	WDW	16.54	70	88.5	575	4.7	1
		184TC	TEFC	CEWDM3615T-5	3,012	WDW	18.04	94	89.5	575	5.3	1
7 1/2	3600	213TC	TEFC	CEWDM3709T-5	4,454	WDW	19.78	143	91.0	575	7.0	10
		213TC	TEFC	CEWDM3710T-5	3,810	WDW	19.78	130	91.7	575	7.6	1
10	3600	215TC	TEFC	CEWDM3711T-5	4,902	WDW	18.64	122	90.2	575	9.5	10
		215TC	TEFC	CEWDM3714T-5	4,331	WDW	21.27	165	91.7	575	9.6	1
15	1800	254TC	TEFC	CEWDM23933T-5	8,517	WDW	23.56	258	92.4	575	14.5	1
20	1800	256TC	TEFC	CEWDM23934T-5	9,877	WDW	23.56	289	91.0	575	19.0	1

Red catalog number indicates **NEW** product

NOTE INDEX MDEX ACC DCPA ACPA GBPA LATH BUFF GRDS DCSW DCPM IMD VSAC BRM UH DP FARM HVAC PUMP XP WD SD GP SP4 INFO TOC

White Washdown, three phase, C-face footless



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
1/3	1800	56C	TENV	VWDM3534	855	WDW	11.05	33	75.5	208-230/460	0.9	1, 12
1/2	1800	56C	TEFC	VFWDM3538	1,116	WDW	12.22	29	78.2	230/460	0.9	1, 12, 30
		56C	TENV	VEWDM3538	1,429	WDW	11.06	20	78.2	230/460	0.9	1, 30
3/4	1800	56C	TENV	VWDM3538	1,069	WDW	11.06	29	78.2	230/460	0.9	1, 12, 30
		56C	TEFC	VFWDM3542	1,207	WDW	12.22	31	82.5	230/460	1.1	1, 12, 30
		56C	TENV	VEWDM3542	1,573	WDW	11.06	32	82.5	230/460	1.1	1, 12, 30
		56C	TENV	VWDM3542	1,161	WDW	11.05	33	82.5	230/460	1.1	1, 12
1	1800	56C	TEFC	VEFWDM3546	1,749	WDW	12.22	38	85.5	230/460	1.6	1, 30
		56C	TENV	VEWDM3546	1,703	WDW	12.06	40	85.5	230/460	1.7	1, 30
		143TC	TEFC	VEFWDM3546T	1,762	WDW	12.28	36	85.5	230/460	1.6	1, 30
1 1/2	1800	143TC	TENV	VEWDM3546T	1,716	WDW	12.12	40	85.5	230/460	1.7	1, 30
		56C	TENV	VEWDM3554	1,828	WDW	12.93	48	86.5	230/460	2.3	30
		145TC	TEFC	VEFWDM3554T	1,890	WDW	13.28	43	86.5	230/460	2.3	1, 30
2	1800	145TC	TENV	VEWDM3554T	1,843	WDW	12.99	48	86.5	230/460	2.3	30
		56C	TEFC	VEWDM3558	1,945	WDW	13.22	46	86.5	230/460	2.8	1, 30
3	1800	143TC	TEFC	VEWDM3558T	1,983	WDW	13.29	47	86.5	230/460	2.8	1, 30
		56C	TEFC	VEWDM3559	2,253	WDW	14.10	50	86.5	230/460	3.6	1, 30
	3600	145TC	TEFC	VEWDM3559T	2,274	WDW	14.16	50	86.5	230/460	3.6	1, 30
		56C	TEFC	VEWDM3561	2,172	WDW	15.61	73	89.5	230/460	4.2	1, 30
		145TC	TEFC	VEWDM3561T	2,197	WDW	15.68	73	89.5	230/460	4.2	1, 30
		145TC	TENV	VEWDM3651T	2,510	WDW	15.63	70	89.5	230/460	4.1	1, 30
182TC	TEFC	VEWDM3611T	2,491	WDW	16.54	73	89.5	230/460	4.2	1, 30		
5	1800	184TC	TEFC	VEWDM3615T	2,824	WDW	18.05	89	89.5	230/460	6.7	1, 30
7 1/2	1800	213TC	TEFC	VEWDM3710T	3,777	WDW	19.78	121	91.7	230/460	9.5	1, 30
10	1800	215TC	TEFC	VEWDM3714T	4,059	WDW	21.27	165	91.7	230/460	12.5	1, 30
575 volt												
1/2	1800	56C	TENV	VWDM3538-5	1,069	WDW	11.06	28	80.0	575	0.8	1, 12
3/4	1800	56C	TENV	VWDM3542-5	1,161	WDW	11.06	32	82.5	575	0.9	1, 12

Red catalog number indicates **NEW** product

White Washdown, three phase, C-face foot mounted, Inverter Duty

Inverter Duty 1000:1 CT
Encoder mounting provisions, Class H insulation, thermostats



Hp	Frame	Encl.	Base Speed	Max Speed	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt													
1	143TC	TENV	1800	2700	IDWNM3546T	2,554	WDW	14.90	41	85.5	230/460	1.7	
1 1/2	145TC	TENV	1800	4500	IDWNM3554T	2,813	WDW	15.78	52	86.5	230/460	2.3	
2	182TC	TENV	1800	6000	IDWNM3609T	3,316	WDW	17.78	77	88.5	230/460	2.9	
3	184TC	TENV	1800	6000	IDWNM3611T	3,376	WDW	19.28	90	89.5	230/460	4.1	
5	213TC	TENV	1800	4000	IDWNM3707T	3,820	WDW	19.84	122	89.5	230/460	6.2	
7 1/2	254TC	TENV	1800	5000	IDWNM22937T	6,804	WDW	23.92	283	91.7	230/460	8.9	
10	254TC	TENV	1800	5000	IDWNM22938T	6,929	WDW	23.92	287	91.7	230/460	12.0	

Red catalog number indicates **NEW** product

White Washdown, three phase, C-face foot mounted, Vector Duty

Inverter Duty 1000:1 CT
HS25 Encoder mounted, Class H insulation, thermostats



Hp	Frame	Encl.	Base Speed	Max Speed	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt													
1	143TC	TENV	1800	2700	ZDWNM3546T	5,116	WDW	14.90	44	85.5	230/460	1.7	
1 1/2	145TC	TENV	1800	4500	ZDWNM3554T	5,375	WDW	15.48	56	86.5	230/460	2.3	
2	182TC	TENV	1800	6000	ZDWNM3609T	5,888	WDW	17.77	71	88.5	230/460	2.9	
3	184TC	TENV	1800	6000	ZDWNM3611T	5,943	WDW	19.27	90	89.5	230/460	4.1	
5	213TC	TENV	1800	4000	ZDWNM3707T	6,386	WDW	19.84	126	89.5	230/460	6.2	
7 1/2	254TC	TENV	1800	5000	ZDWNM22937T	9,332	WDW	23.92	250	91.7	230/460	8.9	
10	254TC	TENV	1800	5000	ZDWNM22938T	9,496	WDW	23.92	286	91.7	230/460	12.0	

Red catalog number indicates **NEW** product

White Washdown, Feather Picker, foot mounted

For feather picker application found in poultry processing plants
Design D, F3 conduit box, labyrinth seal, epoxy encapsulated windings, stainless steel hardware,
shaft extension and nameplate



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
2	1800	145T	TEFC	WDM3558TP	1,951	WDW	14.16	39	82.5	230/460	2.8	30, 31
3	1800	143T	TEFC	WDM3561TP	2,396	WDW	15.53	59	81.5	230/460	4.3	2, 8, 31

White Washdown, Feather Picker, C-face foot mounted

For feather picker application found in poultry processing plants
Design D, F3 conduit box, labyrinth seal, epoxy encapsulated windings, stainless steel hardware,
shaft extension and nameplate



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
3	1800	143TC	TEFC	CWDM3561TP	2,458	WDW	15.54	59	81.5	230/460	4.3	2, 8, 31
575 volt												
3	1800	145TC	TEFC	CWDM3561TP-5	2,458	WDW	15.54	59	81.0	575	3.2	2, 8, 31

White Washdown, Cut Saw, foot mounted

For cut saw application found in poultry processing plants
Design D, F3 conduit box with fully potted leads, labyrinth seal



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
460 volt												
1	1800	D80	TENV	WDNMM3546-4	1,523	WDW	12.00	39	75.5	460	1.5	2, 31

White Washdown, Brake Motor, C-face foot mounted

Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Brake Rating	Notes
230/460 volt													
1/2	1800	56C	TENV	CEWDBM3538	3,435	WDW	15.31	42	78.2	208-230/460	0.9	3	1, 12, 41
3/4	1800	56C	TENV	CEWDBM3542	3,712	WDW	15.31	42	82.5	230/460	1.1	6	1, 12, 30, 41
1	1800	56C	TENV	CEWDBM3546	3,810	WDW	16.31	50	85.5	230/460	1.7	6	1, 30, 41
		143TC	TENV	CEWDBM3546T	3,736	WDW	16.81	51	85.5	230/460	1.7	6	1, 30, 41
1 1/2	1800	145TC	TENV	CEWDBM3554T	4,146	WDW	18.14	61	86.5	230/460	2.3	10	30, 41
2	1800	145TC	TEFC	CEWDBM3558T	4,219	WDW	18.56	60	86.5	230/460	2.8	10	1, 30, 41
3	1800	182TC	TEFC	CEWDBM3611T	5,105	WDW	15.00	93	89.5	230/460	4.2	15	1, 30, 41
5	1800	184TC	TEFC	CEWDBM3615T	6,167	WDW	23.27	110	89.5	230/460	6.7	25	2, 30, 42

White Washdown Jet Pump, three phase, C-face foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
3/4	3600	56J	TEFC	CJWDM3463	1,105	WDW	12.72	33	68.0	208-230/460	1.4	1, 30
1	3600	56J	TEFC	CJEWDM3545	1,741	WDW	12.72	38	78.5	208-230/460	1.6	1, 30
1 1/2	3600	56J	TEFC	CJEWDM3550	1,839	WDW	13.72	41	84.0	208-230/460	2.0	1, 30
2	3600	56J	TEFC	CJEWDM3555	2,040	WDW	13.72	41	85.5	230/460	2.5	1, 30
3	3600	56J	TEFC	CJEWDM3559	2,417	WDW	15.97	64	87.5	208-230/460	3.5	1, 30

White Washdown Jet Pump, three phase, C-face footless



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
3/4	3600	56J	TEFC	JWDM3463	1,097	WDW	12.72	33	68.0	208-230/460	1.4	1, 30
1	3600	56J	TEFC	JEWDM3545	1,732	WDW	12.72	38	78.5	208-230/460	1.6	1, 30
1 1/2	3600	56J	TEFC	JEWDM3550	1,829	WDW	13.72	41	84.0	208-230/460	2.0	1, 30
2	3600	56J	TEFC	JEWDM3555	2,032	WDW	13.72	41	85.5	230/460	2.5	1, 30
3	3600	56J	TEFC	JEWDM3559	2,409	WDW	15.97	64	87.5	208-230/460	3.5	1, 30

White Washdown close-coupled pump, foot mounted

Oversized, double sealed ball bearings
 Locked DE bearing, JM type mechanical seal for pumping



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
Mechanical seal, Type JM												
230/460 volt												
1	3600	143JM	TEFC	JMEWDM3545T	1,800	WDW	15.41	35	84.0	230/460	1.4	1
	1800	143JM	TENV	JMEWDM3546T	1,879	WDW	14.25	39	85.5	230/460	1.7	1, 30
1 1/2	3600	143JM	TENV	JMEWDM3550T	1,889	WDW	14.25	48	85.5	208-230/460	2.0	1, 30
	1800	145JM	TENV	JMEWDM3554T	1,963	WDW	16.50	50	86.5	230/460	2.3	30
2	3600	143JM	TEFC	JMEWDM3555T	2,062	WDW	13.29	47	85.5	208-230/460	2.5	1, 30
	1800	145JM	TEFC	JMEWDM3558T	2,149	WDW	15.41	48	86.5	230/460	2.8	1, 30
3	3600	143JM	TEFC	JMEWDM3559T	2,518	WDW	14.17	50	86.5	230/460	3.6	1, 30
	1800	182JM	TEFC	JMEWDM3611T	2,819	WDW	18.05	70	89.5	230/460	4.2	1, 30
5	3600	184JM	TEFC	JMEWDM3613T	3,323	WDW	18.05	81	88.5	230/460	5.6	1, 30
	1800	184JM	TEFC	JMEWDM3615T	3,175	WDW	19.55	93	89.5	230/460	6.7	1, 30
7 1/2	3600	184JM	TEFC	JMEWDM3616T	3,937	WDW	19.55	96	89.5	230/460	8.4	1, 30
	1800	213JM	TEFC	JMEWDM3710T	3,990	WDW	20.91	151	91.7	230/460	9.5	1, 30
10	3600	215JM	TEFC	JMEWDM3711T	5,083	WDW	20.91	130	90.2	230/460	10.8	1, 30
	1800	215JM	TEFC	JMEWDM3714T	4,242	WDW	22.41	165	91.7	230/460	12.5	1, 30
15	3600	215JM	TEFC	JMEWDM3713T	6,341	WDW	21.64	169	91.0	230/460	17.0	1, 30
	1800	254JM	TEFC	JMEWDM23933T	8,765	WDW	25.06	252	92.4	230/460	18.0	1, 30
20	3600	256JM	TEFC	JMEWDM41906T	10,176	WDW	25.06	255	91.0	230/460	21.5	2
	1800	256JM	TEFC	JMEWDM23934T	10,129	WDW	25.06	275	93.0	230/460	24.0	1, 30
575 volt												
5	3600	184JM	TEFC	JMEWDM3613T-5	3,323	WDW	18.05	74	88.5	575	4.7	10

NOTE INDX MDEX ACC DCPA ACPA GBPA LATH BUFF GRDS DCSW DCPM IMD VSAC BRM UH DP FARM HVAC PUMP XP WD SD GP SP4 INFO TOC

White Washdown Features, three phase 5 thru 75 Hp

IP55

Features

- 300 series stainless steel hardware
- Neoprene gaskets
- Double sealed ball bearings
- Lip and V-Ring seal on DE
- White epoxy, corrosion resistant finish
- Stainless steel shaft extension
- Rugged cast iron construction
- 3 year warranty

Applications

- Packaging
- Food processing
- Pumps and wastewater
- Wet environment

White Washdown Features, three phase, foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
5	900	254T	TEFC	EWDM2280T	8,375	WDW	23.25	256	86.5	230/460	8.6	1, 30
7 1/2	900	256T	TEFC	EWDM2401T	9,080	WDW	23.07	321	86.5	230/460	12.1	1
10	900	284T	TEFC	EWDM2402T	10,112	WDW	27.57	391	89.5	230/460	14.6	1, 30
15	1200	284T	TEFC	EWDM4100T	7,361	WDW	27.57	391	91.7	230/460	21.0	1
	900	286T	TEFC	EWDM2395T	13,498	WDW	27.57	469	89.5	230/460	23.0	1
20	1200	286T	TEFC	EWDM4102T	10,000	WDW	27.57	429	91.7	230/460	26.0	1
	900	324T	TEFC	EWDM4112T	15,388	WDW	30.28	578	90.2	230/460	30.0	1
25	3600	284TS	TEFC	EWDM4107T	7,082	WDW	24.47	265	91.7	230/460	29.0	1
	1800	284T	TEFC	EWDM4103T	6,788	WDW	27.57	437	93.6	230/460	31.0	1
	1200	324T	TEFC	EWDM4111T	10,450	WDW	30.28	605	93.0	230/460	32.0	1
30	900	326T	TEFC	EWDM4116T	19,217	WDW	30.28	578	90.2	230/460	37.0	1, 30
	3600	286TS	TEFC	EWDM4108T	8,633	WDW	24.47	299	91.7	230/460	34.0	1
	1800	286T	TEFC	EWDM4104T	7,909	WDW	27.57	437	93.6	230/460	38.0	1
40	1200	326T	TEFC	EWDM4117T	13,471	WDW	30.28	649	93.0	230/460	39.0	1
	900	364T	TEFC	EWDM4338T	20,320	WDW	33.48	806	91.7	230/460	40.0	
	3600	324TS	TEFC	EWDM4109T	11,859	WDW	28.89	470	92.4	230/460	45.0	1
50	1800	324T	TEFC	EWDM4110T	10,346	WDW	30.28	601	94.1	230/460	48.0	1
	1200	364T	TEFC	EWDM4308T	17,588	WDW	33.48	910	94.1	230/460	49.8	
	900	365T	TEFC	EWDM4348T	23,365	WDW	33.48	910	91.7	230/460	52.9	
60	3600	326TS	TEFC	EWDM4114T	12,427	WDW	28.77	575	93.0	230/460	56.0	1
	1800	326T	TEFC	EWDM4115T	12,144	WDW	30.28	700	94.5	230/460	57.0	1
	1200	365T	TEFC	EWDM4312T	18,734	WDW	33.48	910	94.1	230/460	62.0	
	900	405T	TEFC	EWDM4458T	31,534	WDW	38.19	1216	92.4	230/460	64.3	
60	3600	364TS	TEFC	EWDM4310T	18,894	WDW	31.35	999	93.6	230/460	66.1	

Cast iron frame

Red catalog number indicates **NEW** product

White Washdown Features, three phase, foot mounted

Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
60	1800	364T	TEFC	EWDM4314T	17,827	WDW	33.48	961	95.0	230/460	70.0	
	1200	404T	TEFC	EWDM4403T	25,591	WDW	38.19	1322	94.5	230/460	69.3	
	900	405T	TEFC	EWDM4468T	33,765	WDW	38.19	1216	92.4	230/460	78.4	
75	3600	365TS	TEFC	EWDM4313T	20,354	WDW	31.35	1005	94.5	230/460	80.7	
	1800	365T	TEFC	EWDM4316T	19,381	WDW	33.48	965	95.4	230/460	86.0	
	1200	405T	TEFC	EWDM4404T	31,143	WDW	38.19	1322	94.5	230/460	87.0	
	900	444T	TEFC	EWDM4419T	41,689	WDW	44.97	1815	93.6	230/460	89.3	

Cast iron frame

Red catalog number indicates **NEW** product

TOC
INFO
SP4
GP
SD
WD
XP
PUMP
HVAC
FARM
DP
UH
BRM
VSAC
IMD
DCPM
DCSW
GRDS
BUFF
LATH
GBPA
ACPA
DCPA
ACC
MDEX
INDX
NOTE

White Washdown Features, three phase, C-face foot mounted



Hp	RPM	Frame	Encl.	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
230/460 volt												
5	900	254TC	TEFC	CEWDM2280T	9,335	WDW	23.57	256	86.5	230/460	8.6	1, 30
7 1/2	900	256TC	TEFC	CEWDM2401T	10,040	WDW	23.57	320	86.5	230/460	12.1	1
10	900	284TC	TEFC	CEWDM2402T	11,387	WDW	27.56	391	89.5	230/460	14.6	1, 30
15	1200	284TC	TEFC	CEWDM4100T	8,635	WDW	27.56	447	91.7	230/460	19.4	1
	900	286TC	TEFC	CEWDM2395T	14,772	WDW	27.56	455	89.5	230/460	23.0	1
20	1200	286TC	TEFC	CEWDM4102T	11,275	WDW	27.56	429	91.7	230/460	26.0	1
	900	324TC	TEFC	CEWDM4112T	16,859	WDW	30.28	606	90.2	230/460	30.0	1
25	3600	284TSC	TEFC	CEWDM4107T	8,357	WDW	24.57	307	91.7	230/460	29.0	1
	1800	284TC	TEFC	CEWDM4103T	8,062	WDW	27.56	437	93.6	230/460	31.0	1
	1200	324TC	TEFC	CEWDM4111T	11,920	WDW	30.28	605	93.0	230/460	32.0	1
	900	326TC	TEFC	CEWDM4116T	20,687	WDW	30.28	606	90.2	230/460	37.0	1, 30
30	3600	286TSC	TEFC	CEWDM4108T	9,908	WDW	24.57	299	91.7	230/460	34.0	1
	1800	286TC	TEFC	CEWDM4104T	9,183	WDW	27.56	437	93.6	230/460	38.0	1
	1200	326TC	TEFC	CEWDM4117T	14,942	WDW	30.28	640	93.0	230/460	39.0	1
	900	364TC	TEFC	CEWDM4338T	21,919	WDW	33.48	813	91.7	230/460	40.0	
40	3600	324TSC	TEFC	CEWDM4109T	13,330	WDW	28.89	470	92.4	230/460	45.0	1
	1800	324TC	TEFC	CEWDM4110T	11,816	WDW	30.28	578	94.1	230/460	48.0	1
	1200	364TC	TEFC	CEWDM4308T	19,187	WDW	33.48	914	94.1	230/460	49.8	
	900	365TC	TEFC	CEWDM4348T	24,963	WDW	33.48	920	91.7	230/460	53.0	
50	3600	326TSC	TEFC	CEWDM4114T	13,898	WDW	28.77	575	93.0	230/460	56.0	1
	1800	326TC	TEFC	CEWDM4115T	13,615	WDW	30.28	700	94.5	230/460	58.0	1, 30
	1200	365TC	TEFC	CEWDM4312T	20,333	WDW	33.48	888	94.1	230/460	62.0	
	900	405TC	TEFC	CEWDM4458T	33,533	WDW	38.20	1216	92.4	230/460	64.3	
60	3600	364TSC	TEFC	CEWDM4310T	20,493	WDW	31.35	918	93.6	230/460	66.1	
	1800	364TC	TEFC	CEWDM4314T	19,426	WDW	33.48	961	95.0	230/460	70.0	
	1200	404TC	TEFC	CEWDM4403T	27,590	WDW	38.20	1322	94.5	230/460	69.3	
	900	405TC	TEFC	CEWDM4468T	35,764	WDW	38.20	1216	92.4	230/460	78.4	
75	3600	365TSC	TEFC	CEWDM4313T	21,953	WDW	31.35	1005	94.5	230/460	80.7	
	1800	365TC	TEFC	CEWDM4316T	20,980	WDW	33.48	965	95.4	230/460	86.0	
	1200	405TC	TEFC	CEWDM4404T	33,142	WDW	38.20	1322	94.5	230/460	87.0	
	900	444TC	TEFC	CEWDM4419T	44,327	WDW	44.96	1988	93.6	230/460	89.3	

Cast iron frame

Red catalog number indicates **NEW** product

White Washdown Features, close-coupled pump, foot mounted

Oversized, double sealed ball bearings
 Locked DE bearing, lip and v-ring seal on DE



Hp	RPM	Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Eff.	Voltage	Full Load Amps	Notes
Mechanical seal, Type JM											
230/460 volt											
25	3600	284JM	JMEWDM4107T	8,492	WDW	28.44	446	91.7	230/460	30.0	1
	1800	284JM	JMEWDM4103T	8,197	WDW	28.44	471	93.6	230/460	30.0	1
30	3600	286JM	JMEWDM4108T	10,043	WDW	28.44	459	91.7	230/460	34.0	1, 30
	1800	286JM	JMEWDM4104T	9,318	WDW	28.44	460	93.6	230/460	36.0	1
40	3600	324JM	JMEWDM4109T	13,592	WDW	30.53	618	92.4	230/460	47.0	1
	1800	324JM	JMEWDM4110T	12,078	WDW	30.53	600	94.1	230/460	46.0	1, 30
50	3600	326JM	JMEWDM4114T	14,160	WDW	30.53	635	93.0	230/460	55.0	1
	1800	326JM	JMEWDM4115T	13,876	WDW	30.53	658	94.5	230/460	57.0	1
West coast fit, Type TCZ											
230/460 volt											
60	3600	364TCZ	JMEWDM4310T	21,161	WDW	33.11	900	93.6	230/460	66.1	
	1800	364TCZ	JMEWDM4314T	20,094	WDW	33.11	961	95.0	230/460	70.0	
75	3600	365TCZ	JMEWDM4313T	22,622	WDW	33.11	1005	94.5	230/460	80.7	
	1800	365TCZ	JMEWDM4316T	21,649	WDW	33.11	965	95.4	230/460	86.0	

Cast iron frame

Washdown lead connection kits

Features

- Heat shrink sealed closed-end connector kit (WD5603A01SP)
- Heat shrink connector kit bulk quantity (WD5603A05SP)
- Wirenut kit (WD5600A01SP)
- Provides extra protections against moisture ingress

Applications

- Food processing
- Wet environment
- Conveyors
- Packaging
- Pumps and wastewater

Washdown lead connection kits



Catalog Number	Additional Details	List Price	Disc. Sym.	Aprx. Wt. (lb)
WD5600A01SP	#22 - #8 AWG, Includes 6 wirenuts	43	SVC	1
WD5603A01SP	#18 - #10 AWG, Includes 6 connectors	18	SVC	1
WD5603A05SP	#18 - #10 AWG, Includes 50 connectors	73	SVC	3